

UTILITY PATENT APPLICATION TRANSMITTAL (Only for new nonprovisional applications under 37 C.F.R. § 1.63(b))		Attorney Docket No. P 1744-US2	
		First Inventor or Application Identifier ECKHOUSE, Shimon	
		Title METHOD AND APPARATUS FOR ELECTROMAGNETIC TREATMENT OF THE SKIN, INCLUDING HAIR DEPILOTION	
		Express Mail Label No.	

APPLICATION ELEMENTS See MPEP chapter 800 concerning patent application contents	ADDRESS TO: Assistant Commissioner for Patents Box Patent Application Washington, DC 20231
--	---

1. <input checked="" type="checkbox"/> * Fee Transmittal Form (e.g., PTO/SB/17) (Submit an original and a duplicate for fee processing) 2. <input checked="" type="checkbox"/> Specification [Total Pages 56] (preferred arrangement set forth below) - Descriptive title of the invention - Cross References to Related Applications - Reference to Microfiche Appendix - Background of the invention - Brief Summary of the invention - Brief Description of the Drawings (if filed) - Detailed Description - Claim(s) - Abstract of the Disclosure 3. <input checked="" type="checkbox"/> Drawing(s) (35 U.S.C. 113) [Total Sheets 13] 4. Oath or Declaration [Total Pages 3] a. <input type="checkbox"/> Newly executed (original or copy) b. <input checked="" type="checkbox"/> Copy from a prior application (37 C.F.R. § 1.63(d)) (for continuation/divisional with Box 16 completed) i. <input type="checkbox"/> DELETION OF INVENTOR(S) Signed statement attached deleting inventor(s) named in the prior application, see 37 C.F.R. §§ 1.63(d)(2) and 1.33(b).	5. <input type="checkbox"/> Microfiche Computer Program (Appendix) 6. Nucleotide and/or Amino Acid Sequence Submission (if applicable, all necessary) a. <input type="checkbox"/> Computer Readable Copy b. <input type="checkbox"/> Paper Copy (identical to computer copy) c. <input type="checkbox"/> Statement verifying identity of above copies ACCOMPANYING APPLICATION PARTS 7. <input type="checkbox"/> Assignment Papers (cover sheet & document(s)) 8. <input type="checkbox"/> 37 C.F.R. § 3.73(b) Statement (when there is an assignee) <input type="checkbox"/> Power of Attorney 9. <input type="checkbox"/> English Translation Document (if applicable) 10. <input type="checkbox"/> Information Disclosure Statement (IDS)/PTO-1449 <input type="checkbox"/> Copies of IDS Citations 11. <input checked="" type="checkbox"/> Preliminary Amendment 12. <input type="checkbox"/> Return Receipt Postcard (MPEP 5303) (Should be specifically itemized) 13. <input type="checkbox"/> * Small Entity Statement(s) (PTO/SB/09-12) <input type="checkbox"/> Statement filed in prior application, Status still proper and desired 14. <input type="checkbox"/> Certified Copy of Priority Document(s) (if foreign priority is claimed) 15. <input checked="" type="checkbox"/> Other: <u>postcard</u>
---	---

NOTE FOR ITEMS 1 & 13: IN ORDER TO BE ENTITLED TO PAY SMALL ENTITY FEES, A SMALL ENTITY STATEMENT IS REQUIRED (37 C.F.R. § 1.27) EXCEPT IF ONE FILED IN A PRIOR APPLICATION IS RELIED UPON (37 C.F.R. § 1.28)


16. If a CONTINUING APPLICATION, check appropriate box, and supply the requisite information below and in a preliminary amendment:

<input checked="" type="checkbox"/> Continuation	<input type="checkbox"/> Divisional	<input type="checkbox"/> Continuation-in-part (CIP)	of prior application No. <u>08/912,784</u>
Prior application Information: Examiner <u>E. Winakur</u>			Group/Art Unit: <u>3736</u>

For CONTINUATION or DIVISIONAL APPS only: The entire disclosure of the prior application, from which an oath or declaration is supplied under Box 4b, is considered a part of the disclosure of the accompanying continuation or divisional application and is hereby incorporated by reference. The incorporation can only be relied upon when a portion has been inadvertently omitted from the submitted application parts.

17. CORRESPONDENCE ADDRESS

<input type="checkbox"/> Customer Number or Bar Code		or <input checked="" type="checkbox"/> Correspondence address below	
Name	Citan, Pearl, Latzer & Cohen-Zedek c/o Aquilino, Welsh & Flaxman, P.C.		
Address	2341 Jaffarson Davis Hwy., Suite 112		
City	Arlington	State	VA
Country	USA	Telephone	(703) 920-1122
		Zip Code	22202
		Fax	(703) 920-3399

Name (Print/Type)	Mark S. Cohen	Registration No. (Attorney/Agent)	42,425
Signature		Date	17 February 2000

Burden Hour Statement: This form is estimated to take 0.2 hours to complete. Time will vary depending upon the needs of the individual case. Any comments on the amount of time you are required to complete this form should be sent to the Chief Information Officer, Patent and Trademark Office, Washington, DC 20231. DO NOT SEND FEES OR COMPLETED FORMS TO THIS ADDRESS. SEND TO: Assistant Commissioner for Patents, Box Patent Application, Washington, DC 20231.

PATENT

IN THE UNITED STATES PATENT AND TRADEMARK OFFICE

Applicants:	ECKHOUSE et al.	Examiner:	E. Winakur
Serial No.:	Not yet known	Group Art Unit:	3736
Filed:	Herewith	Attorney Docket No.:	P-1744-US2
Title:	METHOD AND APPARATUS FOR ELECTROMAGNETIC TREATMENT OF THE SKIN, INCLUDING HAIR DEPILOTION		

PRELIMINARY AMENDMENT

Assistant Commissioner for Patents
Washington, DC 20231

Sir:

Please amend the subject application as follows:

In the Specification:

On page 1, line 6, under "Related Applications", please delete the paragraph starting with "This application" and ending at "(pending).", and replace it with --This application is a continuation of United States application Serial No. 08/912,764, filed August 18, 1997; which is a continuation-in-part of United States application Serial No. 08/508,129, filed July 27, 1995, now US Patent No. 5,720,772, issued on February 24, 1998; which is a continuation in part of United States application Serial No. 08/477,479, filed June 7, 1995, now US Patent No. 5,620,478, issued on April 15, 1997; which is a continuation of United States application Serial No. 08/473,532, filed June 7, 1995, now US Patent No. 5,755,751, issued on May 26, 1998; which is a continuation of United States application Serial No. 08/383,509, filed February 3, 1995, now US Patent No. 5,626,631, issued on May 6, 1997; which is a continuation-in-part of United States application Serial No. 07/964,210, filed October 20, 1992, now U.S. Patent No. 5,405,368, issued on April 11, 1995; which are

Applicants: ECKHOUSE et al.
Serial No.: Not yet known
Filed: Herewith


Incorporated herein by reference. United States application Serial No. 08/912,764 is also a continuation-in-part of United States application Serial No. 08/412,519, filed March 29, 1995, now US Patent No. 5,683,380, issued on November 4, 1997, which is incorporated herein by reference.—.

REMARKS

Applicants respectfully request entry of this Amendment.

No fee is deemed necessary for filing this Preliminary Amendment. However, if any fee is necessary, the Undersigned hereby authorizes the US Patent and Trademark Office to charge Deposit Account No. 05-0649.

Respectfully submitted,



Mark S. Cohen
Registration No. 42,425

Eitan, Pearl, Latzer & Cohen-Zedek
c/o AQUILINO, WELSH & FLAXMAN, P.C.
2341 Jefferson Davis Hwy.
Suite 112
Arlington, VA 22202
703/920-3399

Method and Apparatus for Electromagnetic Treatment
of the Skin, Including Hair Depilation

Inventors: Shimon Eckhouse
Hillel Bachrach

Related Applications

This application is a continuation-in-part of prior copending United States application Serial No. 08/508,129 filed July 27, 1995 which is a continuation-in-part of prior copending United States application Serial No. 08/477,479, filed June 7, 1995, entitled "Method And Apparatus For Therapeutic Electromagnetic Treatment," which is a continuation of prior copending United States application Serial No. 08/473,532, filed June 7, 1995, entitled "Method And Apparatus For Therapeutic Electromagnetic Treatment," which are continuations of prior copending United States application Serial No. 08/383,509, filed February 3, 1995, entitled "Method And Apparatus For Therapeutic Electromagnetic Treatment," which is a continuation-in-part of prior co-pending United States application Serial No. 07/964,210, filed October 20, 1992, entitled "Method And Apparatus For Therapeutic Electromagnetic Treatment," issued on April 11, 1995, as U.S. Patent No. 5,405,368. The application is also a continuation-in-part of prior copending United States application Serial No. 08/412,519 filed March 29, 1995 (pending).

Field of the Invention

The present invention relates generally to the art of electromagnetic skin treatment, including devices and methods for removing hair. The invention relates to a method and

apparatus for utilizing a spatially dispersed or extended pulsed light source such as a flashlamp and providing treatment parameters for its use, and also relates to use of devices and methods that utilize electromagnetic energy to kill hair follicles.

Background of the Invention

It is known in the prior art to use electromagnetic radiation in medical applications for therapeutic uses such as treatment of skin disorders. For example, U.S. Patent No. 4,298,005 to Mutzhas describes a continuous ultraviolet lamp with cosmetic, photobiological, and photochemical applications. A treatment based on using the UV portion of the spectrum and its photochemical interaction with the skin is described. The power delivered to the skin using Mutzhas' lamp is described as 150W/m^2 , which does not have a significant effect on skin temperature.

In addition to prior art treatment involving UV light, lasers have been used for dermatological procedures, including Argon lasers, CO_2 lasers, Nd(Yag) lasers, Copper vapor lasers, ruby lasers and dye lasers. For example, U.S. Patent No. 4,829,262 to Furumoto, describes a method of constructing a dye laser used in dermatology applications. Two skin conditions which may be treated by laser radiation are external skin irregularities such as local differences in the pigmentation or structure of the skin, and vascular disorders lying deeper under the skin which cause a variety of skin abnormalities including port wine stains, telangiectasias, leg veins and cherry and spider angiomas. Laser treatment of these skin disorders generally includes localized heating of the treatment area by absorption of laser radiation. Heating the skin changes or corrects the skin disorder and causes the full or partial

disappearance of the skin abnormality.

Certain external disorders such as pigmented lesions can also be treated by heating the skin very fast to a high enough temperature to evaporate parts of the skin. Deeper-lying vascular disorders are more typically treated by heating the blood to a high enough temperature to cause it to coagulate. The disorder will then eventually disappear. To control the treatment depth a pulsed radiation source is often used. The depth the heat penetrates in the blood vessel is controlled by controlling the pulse width of the radiation source. The absorption and scattering coefficients of the skin also affect the heat penetration. These coefficients are a function of the constituents of skin and the wavelength of the radiation. Specifically, the absorption coefficient of light in the epidermis and dermis tends to be a slowly varying, monotonically decreasing function of wavelength. Thus, the wavelength of the light should be chosen so that the absorption coefficient is optimized for the particular skin condition and vessel size being treated.

The effectiveness of lasers for applications such as tattoo removal and removal of birth and age marks is diminished because lasers are monochromatic. A laser of a given wavelength may be effectively used to treat a first type of skin pigmentation disorder, but, if the specific wavelength of the laser is not absorbed efficiently by skin having a second type of disorder, it will be ineffective for the second type of skin disorder. Also, lasers are usually complicated, expensive to manufacture, large for the amount of power delivered, unreliable and difficult to maintain.

The wavelength of the light also affects vascular disorder treatment because blood content in the vicinity of the vascular disorders varies, and blood content affects the

absorption coefficient of the treatment area. Oxyhemoglobin is the main chromophore which controls the optical properties of blood and has strong absorption bands in the visible region. More particularly, the strongest absorption peak of oxyhemoglobin occurs at 418 nm and has a band-width of 60 nm. Two additional absorption peaks with lower absorption coefficients occur at 542 and 577 nm. The total band-width of these two peaks is on the order of 100 nm. Additionally, light in the wavelength range of 500 to 600nm is desirable for the treatment of blood vessel disorders of the skin since it is absorbed by the blood and penetrates through the skin. Longer wavelengths up to 1000nm are also effective since they can penetrate deeper into the skin, heat the surrounding tissue and, if the pulse-width is long enough, contribute to heating the blood vessel by thermal conductivity. Also, longer wavelengths are effective for treatment of larger diameter vessels because the lower absorption coefficient is compensated for by the longer path of light in the vessel.

Accordingly, a wide band electromagnetic radiation source that covers the near UV and the visible portion of the spectrum would be desirable for treatment of external skin and vascular disorders. The overall range of wavelengths of the light source should be sufficient to optimize treatment for any of a number of applications. Such a therapeutic electromagnetic radiation device should also be capable of providing an optimal wavelength range within the overall range for the specific disorder being treated. The intensity of the light should be sufficient to cause the required thermal effect by raising the temperature of the treatment area to the required temperature. Also, the pulse-width should be variable over a wide enough range so as to achieve the optimal penetration depth for each application. Therefore, it is desirable to provide a light source having a wide range of wavelengths, which can be selected

according to the required skin treatment, with a controlled pulse-width and a high enough energy density for application to the affected area.

Pulsed non-laser type light sources such as linear flashlamps provide these benefits. The intensity of the emitted light can be made high enough to achieve the required thermal effects. The pulse-width can be varied over a wide range so that control of thermal depth penetration can be accomplished. The typical spectrum covers the visible and ultraviolet range and the optical bands most effective for specific applications can be selected, or enhanced using fluorescent materials. Moreover, non-laser type light sources such as flashlamps are much simpler and easier to manufacture than lasers, are significantly less expensive for the same output power and have the potential of being more efficient and more reliable. They have a wide spectral range that can be optimized for a variety of specific skin treatment applications. These sources also have a pulse length that can be varied over a wide range which is critical for the different types of skin treatments.

In addition to being used for treating skin disorders, lasers have been used for invasive medical procedures such as lithotripsy and removal of blood vessel blockage. In such invasive procedures laser light is coupled to optical fibers and delivered through the fiber to the treatment area. In lithotripsy the fiber delivers light from a pulsed laser to a kidney or gallstone and the light interaction with the stone creates a shock wave which pulverizes the stone. To remove blood vessel blockage the light is coupled to the blockage by the fiber and disintegrates the blockage. In either case the shortcomings of lasers discussed above with respect to laser skin treatment are present. Accordingly, a treatment device for lithotripsy and blockage removal utilizing a flashlamp would be desirable.

One common method of hair removal, often called electrolysis, is based on the use of "electric needles" that are applied to each individual hair. An electrical current is applied to each hair through the needle. The current heats the hair, causes its carbonization and also causes coagulation of the tissue next to the hair and some coagulation of the micro vessels that feed the hair follicle.

While the electrical needle method can remove hair permanently or long term, its use is practically limited because the treatment is painful and the procedure is generally tedious and lengthy.

Light can also be used effectively to remove hair. For example, other prior art methods of hair removal involve the application of pulsed light, generally from coherent sources such as lasers. R. A. Haric, et al., in U.S. Patent No. 3,693,623, and C. Block, in U.S. Patent No. 3,834,391, teach to remove hair by coagulating single hair with a light coupled to the individual hair by an optical fiber at the immediate vicinity of the hair. Similarly, R. G. Meyer, in U.S. Patent No. 3,538,919, removes hair on a hair by hair basis using energy from a pulsed laser. Similar inventions using small fibers are described in U.S. Patent No. 4,388,924 to H. Weissman, et al. and U.S. Patent No. 4,617,926 to A. Sutton. Each of these teach to remove hair one hair at a time, and are thus slow and tedious.

U.S. Patent No. 5,226,907, to N. Tankovich, describes a hair removal method based on the use of a material that coats the hair and hair follicle. The coating material enhances absorption of energy by the follicles, either by matching the frequency of a light source to the absorption frequency of the material, or by photochemical reaction. In either case the light source is a laser. One deficiency of such a method and apparatus is that lasers can be

expensive and subject to stringent regulations. Additionally, the coating material must be applied only to the hair follicles, to insure proper hair removal and to prevent damage of other tissue.

Light (electromagnetic) energy used to remove hair must have a fluence such that sufficient energy will be absorbed by the hair and the hair follicle to raise the temperature to the desired value. However, if the light is applied to the surface of the skin other than at the precise location of a hair follicle, the light will also heat the skin to coagulation temperature and induce a burn in the skin.

Accordingly, it is desirable to be able to treat the skin by effectively heating multiple follicles, without burning the surrounding skin. Such a method and apparatus should be able to remove more than one hair at a time, and preferably over a wide area of skin, for example at least two square centimeters. Additionally, the method and apparatus should be capable of using incoherent light.

Summary of the Invention

According to a first embodiment of the invention a therapeutic treatment device comprises a housing and an incoherent light source, suitably a flashlamp, operable to provide a pulsed light output for treatment, disposed in the housing. The housing has an opening and is suitable for being disposed adjacent a skin treatment area. A reflector is mounted within the housing proximate the light source, and at least one optical filter is mounted proximate the opening in the housing. An iris is mounted coextensively with the opening. Power to the lamp is provided by a variable pulse width pulse forming circuit. Thus, the treatment device

provides controlled density, filtered, pulsed light output through an opening in the housing to a skin area for treatment.

According to a second embodiment of the invention a method of treatment with light energy comprises the steps of providing a high power, pulsed light output from a non-laser, incoherent light source and directing the pulsed light output to a treatment area. The pulse width of the light output is controlled and focussed so that the power density of the light is controlled. Also, the light is filtered to control the spectrum of the light.

According to a third embodiment of the invention a coupler comprises an incoherent light source such as a toroidal flashlamp. A reflector is disposed around the incoherent light source and at least one optical fiber or light guide. The fiber has an end disposed within the reflector. This end collects the light from the circular lamp. In a similar coupling configuration fibers may be provided, along with a linear to circular fiber transfer unit disposed to receive light from the light source and provide light to the optical fibers. The reflector has an elliptical cross-section in a plane parallel to the axis of the linear flash tube, and the linear flash tube is located at one focus of the ellipse while the linear to circular transfer unit is located at the other focus of the ellipse.

The invention further includes the method of treating the skin to remove hair from an area of tissue by producing electromagnetic energy and applying the energy to the skin. At least one pulse of incoherent electromagnetic energy is preferably used. The incoherent electromagnetic energy is then coupled to an area of the surface of the tissue that includes more than one hair follicle.

Additionally, in one alternative embodiment the energy may, but not necessarily, be

produced by pulsing a flashlamp to generate a pulse having an energy fluence on the order of 10 to 100J/cm². The energy can be coupled through a window in a housing in which the flashlamp is located, by reflecting the energy to the tissue through the window and through a gel located on a surface of the tissue. The window may be brought into contact with the gel. In other alternative embodiments the angular divergence of the electromagnetic energy is controlled, and thus the depth of penetration into the tissue, and the coupling to the hair and to the hair follicles, is also controlled. In another alternative embodiment each step of the method is repeated, but at least two angular divergences are used, thus obtaining at least two depths of penetration.

In other alternative embodiments, electromagnetic energy is filtered. Specifically, in one embodiment the electromagnetic energy is filtered according to the pigmentation level of the tissue to be treated. In another alternative, energy that has a wavelength of less than 550nm and greater than 1300nm is filtered. Some or all of such energy can be filtered.

In yet another alternative embodiment, the pulse produced has a width of less than 200msec, and/or the delay between pulses is on the order of 10 to 100 msec between the pulses. In one embodiment, the surface area of the energy at the tissue is at least two square centimeters.

In accordance with a second aspect of the invention an apparatus for removing hair from an area of tissue that includes more than one hair follicle includes a source of pulsed incoherent electromagnetic energy. The source is located within a housing, and a coupler directs the incoherent electromagnetic energy to the surface of the tissue.

According to an alternative embodiment the source is a flashlamp and a pulse

generating circuit that generates pulses of energy that have an energy fluence on the order of 10 to 100J/cm². The coupler can include a transparent window and the housing a reflective interior, wherein the energy is reflected to the window. A gel is disposed on the surface of the tissue and the window is in contact with the gel, to couple the energy through the window and gel to the surface of the tissue. In another alternative embodiment the energy provided by the coupler has a range of angular divergences.

In another alternative embodiment at least one band pass electromagnetic filter is disposed between the source and the tissue. The filter can be selected such that the wavelength of the energy that passes through the filter is based on the pigmentation level of the treated tissue. Alternatively, the filters pass energy that has a wavelength of between 550nm and 1300nm.

In other embodiments, the source provides pulses having a width of less than 200msec, and/or delays between pulses on the order of 10 to 100 msec. In another embodiment, the area of the energy at the tissue is at least two square centimeters.

According to a third aspect of the invention, a method of removing hair from an area of tissue that has more than one hair follicle includes producing at least one pulse of electromagnetic energy. A gel on a surface of the tissue cools the tissue, but the gel is not adjacent the hair follicle. The electromagnetic energy is coupled to the surface of the tissue.

In one alternative embodiment, the energy is produced by pulsing a flashlamp, and a pulse having an energy fluence on the order of 10 to 100J/cm² is thereby generated. In another embodiment, the flashlamp is located in a housing that includes a transparent window and the energy is reflected through the window and directed through the gel to the tissue. In yet

another alternative embodiment, the angular divergence of the electromagnetic energy is selected to determine the depth of penetration into the tissue, and to determine the coupling to the hair and to the hair follicles. Also, each step of the method may be repeated using at least two different angular divergences, whereby at least two depths of penetration are obtained.

In another alternative embodiment, the electromagnetic energy is filtered. The filtering can be done in accordance with the pigmentation level of the treated tissue. Alternatively, filtering may include filtering some or all of the energy that has a wavelength of less than 550 nm and greater than 1300 nm.

In another alternative embodiment pulses produced have a width of less than 200msec. The delay between pulses may be on the order of 10 to 100 msec. Also, the area of the energy at the tissue can be large, for example more than two square centimeters. The energy may be incoherent, such as that produced by a flashlamp for example, or coherent, such as that produced by a laser, for example.

In accordance with another aspect of the invention, an apparatus for removing hair from an area of tissue that has more than one hair includes a source of pulsed electromagnetic energy. A gel is disposed on the surface of the tissue such that the gel cools the tissue but is not adjacent, and does not cool, the hair follicle. A coupler is disposed between the source and the surface to couple the energy to the surface.

In one alternative embodiment, the source is a pulsed flashlamp that generates pulses having an energy fluence on the order of 10 to 100J/cm². In another alternative, the flashlamp is located in a housing that includes a transparent window and a reflective interior. In yet another alternative embodiment the shape of the coupler determines the angular divergence of

the electromagnetic energy, which determines the depth of penetration of the energy into the tissue, and determines the coupling to the hair and to the hair follicles. The apparatus may include a band-pass filter disposed between the source and the surface. In one alternative the band-pass filter passes energy having a wavelength of between 550nm and 1300nm. The source may be a source of incoherent energy, or a source of coherent energy, such as a laser, for example.

Brief Description of the Drawings

For a better understanding of the invention, reference is made to the accompanying drawings, in which like numerals designate corresponding elements or sections throughout, and in which:

Figure 1 is a cross-sectional view of an incoherent, pulsed light source skin treatment device;

Figure 2 is a side view of the light source of Figure 1;

Figure 3 is a schematic diagram of a pulse forming network with a variable pulse width for use with the skin treatment device of Figures 1 and 2;

Figure 4 is a cross-sectional view of a coupler for coupling light from a toroidal flash tube into an optical fiber with a conical edge;

Figure 5 is a side view of a toroidal flash tube;

Figure 6 is a top view of a toroidal flash tube;

Figure 7 shows the geometry for coupling into a conical section;

Figure 8 is a cross-sectional view of a coupler for coupling light from a toroidal flash

tube into an optical fiber with a flat edge;

Figure 9 is a front sectional view of a coupler for coupling light from a linear flash tube into a circular fiber bundle;

Figure 10 is a side sectional view of the coupler of Figure 9;

Figure 11 is a front view of a coupler for coupling light from a linear flash tube into an optical fiber;

Figure 12 is a front view of a coupler for coupling light from a linear flash tube into a doped optical fiber;

Figure 13 is a schematic configuration of a gel skin interface with a transparent plate;

Figure 14 shows an angular distribution of photons penetrating without using a gel;

Figure 15 shows a light guide providing a large angular divergence;

Figure 16 shows a light guide providing a narrow angular divergence;

Figure 17 shows a spectra produced with a flashlamp current of 200 amps; and

Figure 18 shows a spectra produced with a flashlamp current of 2000 amps; and

Figure 19 shows a GTO driver circuit for a flashlamp.

Figure 20 is a schematic drawing of a cross section of a hair follicle in the dermis and a gel applied to the epidermis in accordance with the present invention;

Figure 21 is a graph showing the optical properties of the skin;

Figure 22 is a side view of a hair removal apparatus constructed in accordance with the present invention;

Figure 23 is a front view of a hair removal apparatus constructed in accordance with the present invention;

Figure 24 is a divergent coupler such as one used in the present invention; and

Figure 25 is a non divergent coupler such as one used in the present invention.

Detailed Description of the Invention and the Preferred Embodiments

Before explaining at least one embodiment of the invention in detail it is to be understood that the invention is not limited in its application to the details of construction and the arrangement of the components set forth in the following description or illustrated in the drawings. The invention is capable of other embodiments or of being practiced or carried out in various ways. Also, it is to be understood that the phraseology and terminology employed herein is for the purpose of description and should not be regarded as limiting.

Referring now to Figures 1 and 2, cross-sectional and side views of an incoherent, pulsed light source skin treatment device 10 constructed and operated in accordance with the principles of the present invention are shown. The device 10 may be seen to include a housing 12, having an opening therein, a handle 13 (Figure 2 only), a light source 14 having an outer glass tube 15, an elliptical reflector 16, a set of optical filters 18, an iris 20 and a detector 22 (Figure 1 only).

Light source 14, which is mounted in housing 12, may be a typical incoherent light source such as a gas filled linear flashlamp Model No. L5568 available from ILC. The spectrum of light emitted by gas filled linear flashlamp 14 depends on current density, type of glass envelope material and gas mixture used in the tube. For large current densities (e.g., 3000 A/Cm² or more) the spectrum is similar to a black body radiation spectrum. Typically, most of the energy is emitted in the 300 to 1000 nm wavelength range.

To treat a skin (or visible) disorder a required light density on the skin must be delivered. This light density can be achieved with the focusing arrangement shown in Figures 1 and 2. Figure 1 shows a cross-section view of reflector 16, also mounted in housing 12. As shown in Figure 1, the cross-section of reflector 16 in a plane is perpendicular to the axis of flashlamp 14 is an ellipse. Linear flashlamp 14 is located at one focus of the ellipse and reflector 16 is positioned in such a way that the treatment area of skin 21 is located at the other focus. The arrangement shown is similar to focusing arrangements used with lasers and efficiently couples light from flashlamp 14 to the skin. This arrangement should not, however, be considered limiting. Elliptical reflector 16 may be a metallic reflector, typically polished aluminum which is an easily machinable reflector and has a very high reflectivity in the visible, and the UV range of the spectrum can be used. Other bare or coated metals can also be used for this purpose.

Optical and neutral density filters 18 are mounted in housing 12 near the treatment area and may be moved into the beam or out of the beam to control the spectrum and intensity of the light. Typically, 50 to 100 nm bandwidth filters, as well as low cutoff filters in the visible and ultraviolet portions of the spectrum, are used. In some procedures it is desirable to use most of the spectrum, with only the UV portion being cut off. In other applications, mainly for deeper penetration, it is preferable to use narrower bandwidths. The bandwidth filters and the cutoff filters are readily available commercially.

Glass tube 15 is located coaxially with flashlamp 14 and has fluorescent material deposited on it. Glass tube 15 will typically be used for treatment of coagulation of blood vessels to optimize the energy efficiency of device 10. The fluorescent material can be chosen

to absorb the UV portion of the spectrum of flashlamp 14 and generate light in the 500 to 650 nm range that is optimized for absorption in the blood. Similar materials are coated on the inner walls of commercial fluorescent lamps. A typical material used to generate "warm" white light in fluorescent lamps has a conversion efficiency of 80%, has a peak emission wavelength of 570 nm and has a bandwidth of 70 nm and is useful for absorption in blood. The few millisecond decay time of these phosphors is consistent with long pulses that are required for the treatment of blood vessels.

Other shapes or configurations of flashlamp 14 such as circular, helical, short arc and multiple linear flashlamps may be used. Reflector 16 may have other designs such as parabolic or circular reflectors. The light source can also be used without a reflector and the required energy and power density may be achieved by locating light source 14 in close proximity to the treatment area.

Iris 20 is mounted in housing 12 between optical filters 18 and the treatment area and controls the length and the width of the exposed area, i.e. by collimating the output of flashlamp 14. The length of flashlamp 14 controls the maximum length that can be exposed. Typically an 8 cm long (arc length) tube will be used and only the central 5 cm of the tube is exposed. Using the central 5 cm assures a high degree of uniformity of energy density in the exposed skin area. Thus; in this embodiment the iris 20 (also called a collimator) will enable exposure of skin areas of a maximum length of 5 cm. The iris 20 may be closed to provide a minimum exposure length of one millimeter. Similarly, the width of the exposed skin area can be controlled in the range of 1 to 5 mm for a 5 mm wide flashlamp. Larger exposed areas can be easily achieved by using longer flash tubes or multiple tubes, and smaller exposure

areas are obtainable with an iris that more completely collimates the beam. The present invention provides a larger exposure area compared to prior art lasers or point sources and is very effective in the coagulation of blood vessels since blood flow interruption over a longer section of the vessel is more effective in coagulating it. The larger area exposed simultaneously also reduces the required procedure time.

Detector 22 (Figure 1) is mounted outside housing 12 and monitors the light reflected from the skin. Detector 22 combined with optical filters 18 and neutral density filters can be used to achieve a quick estimate of the spectral reflection and absorption coefficients of the skin. This may be carried out at a low energy density level prior to the application of the main treatment pulse. Measurement of the optical properties of the skin prior to the application of the main pulse is useful to determine optimal treatment conditions. As stated above, the wide spectrum of the light emitted from the non-laser type source enables investigation of the skin over a wide spectral range and choice of optimal treatment wavelengths.

In an alternative embodiment, detector 22 or a second detector system may be used for real-time temperature measurement of the skin during its exposure to the pulsed light source. This is useful for skin thermolysis applications with long pulses in which light is absorbed in the epidermis and dermis. When the external portion of the epidermis reaches too high a temperature, permanent scarring of the skin may result. Thus, the temperature of the skin should be measured. This can be realized using infra-red emission of the heated skin, to prevent over exposure.

A typical real-time detector system would measure the infra red emission of the skin

at two specific wavelengths by using two detectors and filters. The ratio between the signals of the two detectors can be used to estimate the instantaneous skin temperature. The operation of the pulsed light source can be stopped if a pre-selected skin temperature is reached. This measurement is relatively easy since the temperature threshold for pulsed heating, that may cause skin scarring is on the order of 50°C or more, which is easily measurable using infra-red emission.

The depth of heat penetration depends on the light absorption and scattering in the different layers of the skin and the thermal properties of the skin. Another important parameter is pulse width. For a pulsed light source, the energy of which is absorbed in an infinitesimally thin layer, the depth of heat penetration (d) by thermal conductivity during the pulse can be written as shown in Equation 1:

$$d = 4[k\Delta t / Cp]^{1/2} \quad (\text{Eq. 1})$$

where k= heat conductivity of the material being illuminated;

Δt = the pulse-width of the light pulse;

C = the heat capacity of the material;

p = density of the material.

It is clear from Equation 1 that the depth of heat penetration can be controlled by the pulse-width of the light source. Thus, a variation of pulse-width in the range of 10^{-5} sec to 10^{-1} sec will result in a variation in the thermal penetration by a factor of 100.

Accordingly, the flashlamp 14 provides a pulse width of from 10^{-5} sec to 10^{-1} sec. For treatment of vascular disorders in which coagulation of blood vessels in the skin is the objective the pulse length is chosen to uniformly heat as much of the entire thickness of the vessel as possible to achieve efficient coagulation. Typical blood vessels that need to be treated in the skin have thicknesses in the range of 0.5 mm. Thus, the optimal pulse-width, taking into account the thermal properties of blood, is on the order of 100 msec. If shorter pulses are used, heat will still be conducted through the blood to cause coagulation, however, the instantaneous temperature of part of the blood in the vessel and surrounding tissue will be higher than the temperature required for coagulation and may cause unwanted damage.

For treatment of external skin disorders in which evaporation of the skin is the objective, a very short pulse-width is used to provide for very shallow thermal penetration of the skin. For example, a 10^{-5} sec pulse will penetrate (by thermal conductivity) a depth of the order of only 5 microns into the skin. Thus, only a thin layer of skin is heated, and a very high, instantaneous temperature is obtained so that the external mark on the skin is evaporated.

Figure 3 shows a variable pulse-width pulse forming circuit comprised of a plurality of individual pulse forming networks (PFN's) that create the variation in pulse widths of flashlamp 14. The light pulse full width at half maximum (FWHM) of a flashlamp driven by a single element PFN with capacitance C and inductance L is approximately equal to:

$$\Delta t = 2[LC]^{1/2} \quad (\text{Eq. 2})$$

Flashlamp 14 may be driven by three different PFN's, as shown in Figure 3. The relay contacts R1', R2' and R3' are used to select among three capacitors C1, C2 and C3 that are charged by the high voltage power supply. Relays R1, R2 and R3 are used to select the PFN that will be connected to flashlamp 14. The high voltage switches S1, S2 and S3 are used to discharge the energy stored in the capacitor of the PFN into flashlamp 14. In one embodiment L1, L2 and L3 have values of 100 mH, 1 mH and 5 mH, respectively, and C1, C2 and C3 have values of 100 mF, 1 mF and 10 mF, respectively.

In addition to the possibility of firing each PFN separately, which generates the basic variability in pulse-width, additional variation can be achieved by firing PFN's sequentially. If, for example, two PFN's having pulse-width Δt_1 and Δt_2 are fired, so that the second PFN is fired after the first pulse has decayed to half of its amplitude, then an effective light pulse-width of this operation of the system will be given by the relation: $\Delta t = \Delta t_1 + \Delta t_2$.

The charging power supply typically has a voltage range of 500 V to 5 kV. The relays should therefore be high voltage relays that can isolate these voltages reliably. The switches S are capable of carrying the current of flashlamp 14 and to isolate the reverse high voltage generated if the PFN's are sequentially fired. Solid-state switches, vacuum switches or gas switches can be used for this purpose.

A simmer power supply (not shown in Figure 3) may be used to keep the flashlamp in a low current conducting mode. Other configurations can be used to achieve pulse-width variation, such as the use of a single PFN and a crowbar switch, or use of a switch with closing and opening capabilities.

Typically, for operation of flashlamp 14 with an electrical pulse-width of 1 to 10msec, a linear electrical energy density input of 100 to 300 J/cm can be used. An energy density of 30 to 100 J/cm² can be achieved on the skin for a typical flashlamp bore diameter of 5 mm. The use of a 500 to 650 nm bandwidth transmits 20% of the incident energy. Thus, energy densities on the skin of 6 to 20 J/cm² are achieved. The incorporation of the fluorescent material will further extend the output radiation in the desired range, enabling the same exposure of the skin with a lower energy input into flashlamp 14.

Pulsed laser skin treatment shows that energy densities in the range of 0.5 to 10 J/cm² with pulse-widths in the range of 0.5 msec are generally effective for treating vascular related skin disorders. This range of parameters falls in the range of operation of pulsed non-laser type light sources such as the linear flashlamp. A few steps of neutral density glass filters 18 can also be used to control the energy density on the skin.

For external disorders a typical pulse-width of 5 microsecond is used. A 20 J/cm electrical energy density input into a 5 mm bore flashlamp results in an energy density on the skin of 10 J/cm². Cutting off the hard UV portion of the spectrum results in 90% energy transmission, or skin exposure to an energy density of close to 10 J/cm². This energy density is high enough to evaporate external marks on the skin.

Device 10 can be provided as two units: a lightweight unit held by a physician using handle 13, with the hand-held unit containing flashlamp 14, filters 18 and iris 20 that together control the spectrum and the size of the exposed area and the detectors that measure the reflectivity and the instantaneous skin temperature. The power supply, the PFN's and the electrical controls are contained in a separate box (not shown) that is connected to the hand-

held unit via a flexible cable. This enables ease of operation and easy access to the areas of the skin that need to be treated.

The invention has thus far been described in conjunction with skin treatment. However, using a flashlamp rather than a laser in invasive treatments provides advantages as well. Procedures such as lithotripsy or removal of blood vessel blockage may be performed with a flashlamp. Such a device may be similar to that shown in Figures 1 and 2, and may use the electronics of Figure 3 to produce the flash. However, to properly couple the light to an optical fiber a number of couplers 40, 80 and 90 are shown in Figures 4 and 8-10, respectively.

Coupler 40 includes an optical source of high intensity incoherent and isotropic pulsed light such as a linear flash tube 42, a light reflector 44 which delivers the light energy to an optical fiber 46. The latter has a generally conical edge in the embodiment of Figure 4. Optical fiber 46 transfers the light from light collection system 44 to the treatment area. In general, coupler 40 couples pulsed light from a flash tube into an optical fiber and has applications in medical, industrial and domestic areas.

For example, coupler 40 may be used in material processing to rapidly heat or ablate a portion of a material being processed, or to induce a photo-chemical process. Alternatively, coupler 40 may be used in a photography application to provide a flash for picture taking. Using such a coupler would allow the flash bulb to be located inside the camera, with the light transmitted to outside the camera using an optical fiber. As one skilled in the art should recognize coupler 40 allows the use of incoherent light in many applications that coherent or incoherent light has been used in the past.

To provide for coupling the light to an optical fiber, flash tube 42 has a toroidal shape, shown in Figures 5 and 6, and is disposed inside reflector 44. In addition to the toroidal shape other shapes, such as a continuous helix, may be used for flash tube 42. However, a helical tube is more difficult to manufacture than a toroidal tube. Referring now to Figure 6, flash tube 42 is generally in the shape of a torus, but is not a perfect torus since the electrodes located at the end of the torus have to be connected to the power source. This does not create a significant disturbance in the circular shape of flash tube 42, since the connection to the electrodes can be made quite small.

Reflector 44 collects and concentrates the light, and has a cross-section of substantially an ellipse, in a plane perpendicular to the minor axis of the toroidal flash tube 42. The major axis of this ellipse preferably forms a small angle with the major axis of toroidal lamp 42. The exact value of the angle between the ellipse axis and the main axis of lamp 42 depends on the Numerical Aperture (NA) of the optical fiber. The toroidal flash tube is positioned so that its minor axis coincides with the focus of the ellipse. The other focus of the ellipse is at the edge of optical fiber 46. Reflector 44 may be machined from metal with the inner surfaces polished for good reflectivity. Aluminum is a very good reflector with high reflectivity in the visible and ultraviolet wavelengths, and it may be used for this purpose. The reflector can be machined in one piece and then cut along a surface perpendicular to the main axis of the device. This will enable integration of the toroidal flash tube into the device.

As shown in Figure 4, the edge of optical fiber 46 is a cone with a small opening angle, so that the total area of the fiber exposed to the light from the flash tube is increased. Referring now to Figure 7 the geometry for coupling light into a conical tip is shown. It is

assumed here that the light comes from a region in space with a refractive index of n and that the conical section of the fiber (as well as the rest of the fiber core) has a refractive index of n_1 .

Not all the light rays hitting the cone are trapped in it. For light rays that propagate in a plane that contains the major axis of the system, a condition can be derived for the angle of a ray that will be trapped and absorbed in the fiber. This condition is shown in Equation 3.

$$\sin(\mu_{\text{crit}}) = \cos(\beta) - [n_1^2/n_2^2 - 1]^{1/2} \sin(\beta) \quad (\text{Eq. 3})$$

Light will be trapped in the conical portion of the optical fiber if the incidence angle μ is larger than μ_{crit} calculated from Equation 3. Trapping is possible only if $n_1 > n_2$. If the medium outside of the fiber is air, $n_2 = 1$.

Not all of the light trapped in the conical section of the fiber will also be trapped in the straight portion of the fiber if a fiber with a core and a cladding is used. If a fiber with a core and no cladding is used (air cladding), then all the rays captured in the conical section of the fiber will also be trapped in the straight section of the fiber.

The configuration shown in Figure 4 can also be used with a fluid filling the volume between the reflector and the optical fiber. A very convenient fluid for this purpose may be water. Water is also very effective in cooling the flashlamp if high repetition rate pulses are used. The presence of a fluid reduces the losses that are associated with glass to air transitions, such as the transition between the flashlamp envelope material and air.

If a fluid is used in the reflector volume, then its refractive index can be chosen such that all the rays trapped in the conical section are also trapped in the fiber, even if core/cladding fibers are used.

Another way of configuring the fiber in the reflector is by using a fiber with a flat edge. This configuration is shown in Figure 8 and has trapping efficiency very close to the trapping efficiency of the conical edge. Many other shapes of the fiber edge, such as spherical shapes, can also be used. The configuration of the fiber edge also has an effect on the distribution of the light on the exit side of the fiber and it can be chosen in accordance with the specific application of the device.

The device may be used with a variety of optical fibers. Single, or a small number of millimeter or sub-millimeter diameter fibers, will typically be used in invasive medical applications. In other applications, particularly in industrial and domestic applications, it may be preferable to use a fiber having a larger diameter, or a larger bundle of fibers, or a light guide.

According to one embodiment flexible or rigid light guides are used to couple the light to the treatment area. Flexible light guides made from a bundle of quartz or other glass fibers that are fused together by heat at the edge of the bundles. The bundles may be circular, rectangular, or any other useful shape. Rigid light guides may be made from quartz, acrylic, glass, or other materials having a high degree of transparency. The material is generally highly polished on all sides.

A typical cross section of a circular light guide useful for therapeutic treatment is one mm to ten mm in diameter. Alternatively, a rectangular light guide may be used having

typical dimensions of 3 mm by 10 mm to 40 mm by 100 mm. In either case the length may be 20 to 300 mm, or as needed for the specific application.

According to another alternative embodiment a rectangular light guide is used to more efficiently couple the light. The rectangular light guide is chosen to have a shape that matches a rectangular linear flashlamp and to match the shape of the vessel being treated.

The light guides described above may be used in another alternative embodiment to control the spectrum of light delivered to the treatment area. Spectral control can be achieved by making the light guide from a material that had an absorbing dye dissolved therein. Thus, light transmitted by the light guide will have a spectrum in as determined by the absorbing dye. Alternatively, a flat, discrete filter may be added to one end (preferably the input end) of the light guide. Both of these filters are absorbing filters. The inventors have found that absorbing filters produced by Schott, having Model Nos. OG515, OG550, OG570, and OG590 have suitable characteristics.

Additionally, interference filters or reflective coatings on the light guide may be used by applying a proper optical coating to the light guide. Again, a single discrete interference filter could also be used. Additionally, combinations of the various filters described herein, or other filters, may be used. The use of the filters described here may render the use of the filters described earlier with reference to Figure 1 redundant.

An alternative embodiment entails the use of application specific light guides. In this way the spectra of light for various treatments can be easily controlled. According to this alternative each type of treatment will be performed with a specific light guide.

The optical properties of the light guide will be chosen to optimize the particular

treatment. The wavelengths below are particularly useful for the respective treatments:

arteries less than 0.1 mm in diameter - 520-650 nm

veins less than 0.1 mm in diameter - 520-700 nm

vessels between 0.1 and 1.0 mm in diameter - 550-1000 nm

larger vessels - 600-1000 nm

In each case if the skin is darker (higher pigmentation) longer wavelengths on the lower cut-off portion of the spectrum should be used.

Multiple spectra may be used for optimal penetration. This may be accomplished by illuminating with a few pulses, each having a different spectrum. For example, the first pulse can have a spectrum that is highly absorbed in blood. This pulse will coagulate the blood, thereby changing the optical properties of the blood, making it more absorbing in another wavelength range (preferably longer). A second pulse will be more efficiently absorbed since the blood absorbs energy of a greater wavelength range. This principle may be used with lasers or other light sources as well.

In addition to the features of the light guides discussed above, a light guide is used, in one alternative embodiment, to control the angular distribution of the light rays impinging on the skin. Light that impinges on the skin at large angles (relative to the perpendicular) will not penetrate very deeply into the tissue. Conversely, light that impinges perpendicularly to the skin will have a deeper penetration. Thus, it is desirable to provide a distribution of light rays that has a relatively wide angular divergence when the treatment requires shallow

penetration. Alternatively, a narrow divergence is preferable for treatment requiring deep penetration is desired. Some treatment might require both shallow and deep penetration.

Figure 15 shows a light guide 115 having an exit beam with a greater angular divergence than that of the entrance beam. As shown in Figure 15, a beam 116 enters light guide 115 at a small angle, relative to the axis of light guide 115. When beam 501 exits light guide 115, the angle, relative to the axis, is much greater. The tapered shape of light guide 115 enhances this divergence.

Figure 16 shows a straight light guide 118 that maintains the angular distribution of the rays of light that enter into it. A beam 119 is shown entering and exiting light guide 118 with the same angle, relative to the axis of coupler 601. Alternate use of both light guides 115 and 118 can achieve the narrow and deep penetration discussed above. Alternatively, the user can select the type of coupler according to the depth of penetration needed for the treatment being performed.

Figures 9 and 10 show a coupler 90 for coupling a linear flash tube 92 through a linear to circular fiber transfer unit 94 to a fiber bundle 96. A reflector 98 has an elliptical cross-section, shown in Figure 10, in a plane parallel to the axis of linear flash tube 92 in this embodiment. Tube 92 is located on one focus of the ellipse while the linear side of linear to circular bundle converter is located at the other focus of the ellipse. This configuration is relatively simple to manufacture and commercially available linear to circular converters such as 25-004-4 available from General Fiber Optics may be used. This configuration is particularly useful for larger exposure areas of the fiber, or for flash illumination purposes.

The energy and power densities that can be achieved by this invention are high

enough to get the desired effects in surface treatment or medical applications. For the embodiment shown in Figure 4 the total energy and power densities can be estimated as follows. For a typical toroidal lamp with a 4 mm bore diameter and a major diameter of 3.3 cm an electrical linear energy density input of 10 J/cm into the lamp can be used with a 5 μ sec pulse width. The light output of the lamp will be 5 to 6 J/cm for optimal electrical operating conditions. For the reflector shown in Figure 4, 50% of the light generated in the lamp will reach the lower focus. Thus, a total energy flux on the focus of 25 to 30 J may be obtained. For embodiments shown in Figure 4 or Figure 8 the total cross-section area of reflector at the focal plane has a cross-section of 0.8 cm². Energy densities on the order of 30 to 40 J/cm² at the entrance to the fiber should be attained with this cross-section. This corresponds to power densities of 5 to 10 MW/cm², which are the typical power densities used in medical or material processing applications.

For longer pulses, higher linear electrical energy densities into the lamp can be used. For a 1 msec pulse to the flash tube a linear electrical energy density of 100 J/cm can be used. The corresponding energy density at the focal area would be up to 300 J/cm². Such energy densities are very effective in industrial cleaning and processing applications as well as in medical applications.

Alternative embodiments for coupling the optical fiber to an extended light source such as a linear flashlamp are shown in Figures 11 and 12. In the embodiment of Figure 11 an optical fiber 101 is wound around a lamp 102 and a lamp envelope 103. Some of the light that is produced by the light source is coupled into the fiber. If the light rays are propagating in the direction that is trapped by the fiber then this light will propagate in the fiber and it

can be used at a fiber output 104. One limitation of this configuration is the fact that most of the light emitted by lamp 103 travels in a direction perpendicular to the surface of lamp 103 and cannot be trapped in fiber 101.

The embodiment shown in Figure 12 overcomes this problem. A doped optical fiber 105 is wound around lamp 102 and envelope 103, rather than an undoped fiber such as fiber 101 of Figure 11. The dopant is a fluorescent material which is excited by the radiation emanating from lamp 102 and radiates light inside the fiber. This light is radiated omnidirectionally and the part of it that is within the critical angle of fiber 105 is trapped and propagates through the fiber and can be used at fiber output 104. The angle of light that is trapped in the fiber is the critical angle of the material from which the optical fiber or optical wave guide is made. For a fiber (or optical wave guide) in air this angle is given by $\sin \alpha = 1/n$.

Typically for glass or other transparent materials $n = 1.5$ and $\alpha = 41.8^\circ$. This corresponds to a trapping efficiency of more than 10% of the light emitted by fluorescence inside the fiber. If we assume a 50% efficiency of the fluorescence process we find out that more than 5% of the light produced by the lamp is trapped and propagated down the fiber. For example, a 4" lamp with a linear electrical energy input of 300 J/inch and 50% electrical to light conversion efficiency would couple 2.5% of its electrical energy into the fiber. This corresponds, for the 4" lamp case to a total light energy of 30 J of light. This embodiment has the additional advantage of transferring the wavelength emitted by the lamp to a wavelength that may be more useful in some of the therapeutic or processing applications mentioned before. Thus, fluorescent material doped in the fiber can be chosen in accordance

with an emission wavelength determined by the specific application of the device.

One alternative embodiment includes the use of a gel to couple the light to the skin. This alternative reduces heating of the outer layer of the skin (the epidermis and upper layers of the dermis). The gel is preferably a high viscosity water based gel and is applied to the skin before treatment, although other gels that are not necessarily water based may be used. A gel having a relatively high heat capacity and thermal conductivity, such as a water based gel, is preferable to enable cooling of the outer skin (the epidermis in particular). Transparency is also desirable because during treatment light passes through the transparent gel and reaches the skin.

Referring now to Figure 13, a gel 110 is applied to the skin 21 prior to the treatment. A flat layer of gel on top of the skin is used since irregularities in the upper layer of the gel through which the light passes may cause scattering of the light and reduce its penetration into the skin. In order to achieve this flatness a solid, transparent, flat piece 111 may be applied on top of the skin. The configuration is shown schematically in Figure 13. The transparent plate can be made out of glass or other transparent materials. Either the flashlamp housing or the light guides discussed above may be placed in direct contact with the transparent plate.

The configuration of Figure 13 has the advantage of reducing the scattering of light (represented by arrows 113) that enters into the skin due to irregularities in the surface of the skin. The skin has an index of refraction that is larger than that of the air. As a result, any photon that impinges on the air skin interface is deflected if it does not hit the skin at an incidence angle of 0° . Since the surface of the skin is irregular the angular distribution of the

skin increases. This is shown schematically in Figure 14.

The use of gel addresses this problem since the gel can fill irregular voids that are created by the skin structure. The transparent plate that covers the gel and the gel itself will preferably have an index of refraction that is close to that of the skin. This is relatively easy since the index of refraction of the skin is of the order of 1.4 in the visible and the near infrared. Most glasses and transparent plastics have indices of refraction that are of the order of 1.5 which is close enough. The index of refraction of water is of the order of 1.34 in this range. Water based gels will have similar indices of refraction. The index can be increased by proper additives. The plate and gel thus act as a flat surface for the light to impinge upon. Because the gel and plate have an index of refraction close to that of the skin there is very little scattering at the gel-plate and gel skin interfaces.

The use of a gel has been experimentally successful in the treatment of leg veins and other benign vascular lesions of the skin. The treatments were carried out with the flashlamp described above. However, in alternative embodiments a different incoherent source, or a coherent source, may be used.

During operation light is typically applied to the skin in a sequence of three pulses with short delays between the pulses. This mode of operation is used in order to take advantage of the faster cooling of the superficial, thin (less than 0.1 mm thick) epidermis compared to the larger and deeper vessels typical of leg veins. The gel in contact with the skin cools the epidermis during the waiting period between the pulses. This cooling reduces significantly the damage to the epidermis.

In accordance with the invention, light is applied to the treated area in either a long

pulse or in a sequence of pulses separated by a delay. The delay and/or pulse length is preferably controlled by the operator to provide enough heat to accomplish the desired treatment but not enough heat to damage the skin.

This concept was tested with large and deep vessels (of the order of 2 mm in diameter and 2 mm deep). A thin layer of commercial water based ultrasound gel (1 to 2 mm thick, "Aqua clear" gel made by Parker USA) was applied on the skin. A 1mm thin glass window was used to generate a flat layer of the gel. The light from the device passed through the thin glass and the gel and into the skin. Care was taken to assure than no air bubbles exist in the gel. This configuration was tested with photon fluences of 30 to 50 J/cm². Coagulation and clearance of the vessels was obtained without causing damage to the skin. This is contrary to similar trials in which gel was not used and in which fluences of 20J/cm² with the same pulse structure caused burns of the skin.

The epidermis has a thickness of approximately 0.1 mm and a cooling time of about 5 msec. Thus, to avoid burning delays greater than 5 msec are used.

In another alternative embodiment the spectrum of the light used for treatment is controlled by controlling the voltage and/or current applied to the flashlamp. As is well known in the art, the spectrum of light produced by a flashlamp is dependent on the voltage and current provided to the flashlamp. According to this embodiment the input voltage and current is selected to provide a desired treatment spectrum. The appropriate voltage and currents may be determined experimentally for each flashlamp used.

For example, a flashlamp current of 200 amps produced the spectra shown in Figure 17. Similarly, the spectra of Figure 18 was produced using a flashlamp current of 380 amps.

The spectra of Figure 17 shows a significant enhancement in the wavelength range of 800-1000 nm. Such a spectra is particularly useful for treatment of large vessels.

The different currents and voltages used to control the output spectra may be obtained using a group or bank of capacitors that are capable of being connected in either series or parallel as part of the power source for the flashlamp. A series connection will provide a relatively high voltage and high current, thereby producing a spectra having energy in a shorter wavelength, such as 500-600 nm. Such a series connection will be more appropriate for generating shorter pulses (1 to 10 msec, e.g.) useful for treatment of smaller vessels.

A parallel connection provides a lower current and voltage, and thus produces an output spectra of a longer wavelength, such as 700-1000 nm. Such a spectra is more appropriate for treatment of larger vessels and is suitable for producing longer pulses (in the range of 10-50 msec, e.g.). The selection of series or parallel connections may be done using a relay or sets of relays.

In one alternative embodiment the pulse forming network of Figure 3 is replaced by a GTO driver circuit 121, such as that shown in Figure 19. The driver circuit of Figure 19 uses a switch capable of being turned both on and off to control the application of power to the flashlamp. While this alternative embodiment will be described with respect to a GTO being used as the switch, other switches capable of being turned both on and off, such as IGBTs, may also be used.

Referring now to Figure 19, driver circuit 121 includes a high voltage source 122, a capacitor bank C5, an inductor L5, a diode D5, a switch GTO1, a diode D6, a diode D7, a resistor R5, a capacitor C6, a GTO trigger generator TR1, a resistor R7, a capacitor C7 and a

flashtube trigger generator TR2. These components are connected to flashlamp 14 and serve to provide the power pulses to flashlamp 14. The duration and timing of the pulses are provided in accordance with the description herein. Driver 121 operates in the manner described below.

* High voltage source 122 is connected across capacitor bank C5, and charges capacitor bank C5 to a voltage suitable for application to flashlamp 14. Capacitor bank C5 may be a comprised of one or more capacitors, and may be configured in the manner described above.

Prior to illumination of flashlamp 14 flashtube trigger generator TR2 breaks down flashlamp 14 and creates a relatively low impedance channel therein. After the flashlamp breaks down, capacitor C7 dumps current into flashlamp 14, further creating a low impedance channel in flashlamp 14. In this manner a pre-discharge is provided that prepares flashlamp 14 for the power pulse. Capacitor C7 provides a small amount of current, relative to capacitor bank C5. Alternatively, driver circuit 121 may operate in a simmer mode, wherein the pre-discharge is not necessary.

Thereafter, switch GTO1 is turned on via a pulse from GTO trigger generator TR1, completing the circuit between flashlamp 14 and capacitor bank C5. Thus, capacitor bank C5 discharges through flashlamp 14. An inductor L5 may be provided to control the rise time of the current through flashlamp 14. Inductor L5 may include an inherent resistive component, not shown.

After a length of time determined by the desired pulse width has passed, GTO trigger generator TR1 provides a pulse to switch GTO1, turning it off. A control circuit determines the timing of the trigger pulses and provides them in accordance with the desired pulse widths

and delays.

A snubber circuit comprised of diode D6, resistor R5, and a capacitor C6 is provided for switch GTO1. Also, diodes D5 and D7 are provided to protect switch GTO1 from reverse voltages. Resistor R7 is provided in parallel with flashlamp 14 to measure the leakage current of switch GTO1, which can in turn be used to make sure that switch GTO1 is operating properly.

A possible addition to driver circuit 121 is to provide an SCR or other switch in parallel with capacitor bank C5. This allows the discharge or resetting of capacitor bank C5 without turning on switch GTO1. Other modifications may be made, such as providing the circuit with a serial trigger, rather than the parallel trigger shown. Another modification is to use the driver circuit with a laser rather than flashlamp 14.

Proper use of pulse widths and delays can aid in avoiding burning the epidermis. The epidermis has a cooling time of about 5 msec, while large vessels have a longer cooling time (a 1 mm vessel has a cooling time of about 300 msec). Thus, during a pulse of duration longer than 5 msec the epidermis can cool down but the vessel will not. For example, for treatment of a large vessel (such as one having a diameter of about 1 mm a pulse of 100 msec will allow the skin to cool, but the vessel will not cool.

The same effect may be achieved using trains of pulses. This is useful when it is not practical to provide a single long pulse to the flashlamp. The delays between pulses are selected to allow the skin to cool, but to be too short for the vessel to cool. Thus, larger vessels can be treated with longer delays because they have greater cooling times. Small vessels cool quickly and long delays are not effective. However, they also need less energy

and can be treated effectively in a single pulse. Typical delay times are in the range of 20 msec to 500 msec. More specifically, delays of between 100-500 msec are effective for vessels larger than 1 mm in diameter.

Delays of between 20-100 msec are effective for vessels between 0.5 and 1 mm in diameter. Delays of between 10-50 msec are effective for vessels between 0.1 and 0.5 mm in diameter. A single pulse having a width in the range of 1 msec to 20 msec is effective for vessels less than 0.1 mm diameter.

Additionally, delays should be selected according to skin pigmentation. Darker skin absorbs more energy and needs more time to cool; thus longer delays are needed. Lighter skin absorbs less energy and can accommodate shorter delays.

It has been found that multiple pulses avoids "purpura" or the explosion of small vessels in or close to the skin. The use of pulses to avoid burning and provide cooling will be effective for light provided by lasers or other sources as well.

Another alternative embodiment includes the use of a microprocessor or personal computer to control the flashlamp. The microprocessor can be used to provide the timing functions and prompt the trigger signals described above. Additionally, in one embodiment the microprocessor includes a user interface, such as a screen and keyboard, buttons, mouse, or other input device. The microprocessors have information stored therein that aids in the selection of treatment parameters.

For example, if the condition being treated is a port wine stains skin type III, the physician inputs that condition into the microprocessor. The microprocessor responds with suggested treatment parameters, such as using a 570 nm cut-off filter, a double pulse with a

delay of 50 msec and a fluence of 55 J/cm². The physician can alter these suggested parameters, but need not refer back to operating guidelines for suggested parameters. This alternative may be used with light sources other than a flashlamp, such as UV or a pulsed laser.

These output parameters are shown on a display such as a screen or printer, and include the outputs discussed below. This will aid the physician in determining the proper treatment and in learning how to effectively use such devices. In one embodiment the microprocessor output on the display shows a simulation of interaction of light with skin and vascular lesions, oxygen concentration and temperature distribution in malignant tissue being illuminated for the purpose of cancer by a flashlamp, or processes occurring in skin resurfacing using infrared lasers or other sources.

A program within the microprocessor (or alternatively an analog circuit) models interaction of light with tissue and vessels. Many programs may be used to carry out the modeling, and in the preferred embodiment the following input parameters are used: light source type (flashlamp or pulsed laser e.g.); number of output curves (1-4 e.g.); skin type; vessel diameter and depth; blood type (oxy or deoxy-hemoglobin); pulse duration; delay between pulses; energy fluence; type of filter; short or long pulse mode; is a gel being used and its temperature. For a pulsed laser the wavelength is an input (400-1064 nm e.g.).

The microprocessor and the screen show the following information in one embodiment: temperature distribution in the tissue and in the vessel at the end of treatment; graphs of up to four curves to compare different light sources or treatment regime. Alternatively, the outputs could be printed rather than shown on a

screen.

One skilled in the art will recognize that many microprocessor routines may be used to implement the invention. The routines may model the interactions in many ways, and one such model for single dimensional light interaction with a tissue uses the following empirical expression for fluence:

$$F=F(0)\exp(-x/d)$$

where $d = 1/\mu_{\text{eff}}$ and

$$\mu_{\text{eff}} = [3\mu_a(\mu_s + \mu_s(1-g))]^{1/2}$$

Where μ_a is an absorption coefficient of dermis, μ_s is a scattering coefficient of dermis, and g is the anisotropy factor which is defined as average cosine of scattering angle for one scattering event.

$F(0)$ was calculated in accordance with *Diffusion of Light in Turbid Material*, A. Ishimaru, Applied Optics, 1989 Vol. 28 No. 12, pp 2210-2215, but an empirical correction depending on wavelength is added:

$$F(0)=F_0(640/W)^{1/4} \quad \text{where } W \text{ is a wavelength.}$$

Light relaxation time in the tissue is significantly less than the temperature relaxation time and light pulse durations used for treatment of skin lesions, therefore a stationary model

for description of light penetration into the tissue was used. Ishimaru's hydrodynamic model is suitable for calculating of $F(0)$. Accordingly to this model, the diffuse energy fluence rate ψ_d satisfies the following diffusion equation:

$$(\nabla^2 - K^2) \psi_d = -Q$$

$$Q = 3\gamma_s (\gamma_T + g\gamma_a) F_0 \exp(-\tau)$$

$$K^2 = 3\gamma_s \gamma_a$$

$$\gamma_a = \gamma_s (1-g) + \gamma_a$$

$$\gamma_s = \gamma_a + \gamma_s$$

$$\tau = \int \gamma_s ds$$

where F_0 is the incident energy beam. Scattering and absorption coefficients are functions of wavelength. The total energy fluence rate is given by

$$\psi_t = \psi_d + \psi_c$$

$$\psi_c = F_0 \exp(-\tau)$$

This equation was calculated numerically with the corresponding boundary conditions. The boundary condition for ψ_d at the surface illuminated by the incident intensity is

$$\psi_d + 2/3\gamma_s \cdot \psi_d + 2\gamma_s g F_0 / \gamma_s = 0$$

Temperature distribution behavior in the tissue is described by solution of the 1-D heat conductivity equation in planar geometry for near epidermis area

$$\rho c \cdot \partial T / \partial t = \lambda \partial^2 T / \partial x^2 + \gamma_s \psi_s$$

with initial and boundary conditions

$$T_{T=0} = 36$$

$$\partial T / \partial x_{x=0} = 0$$

Here ρ is the density of tissue, c is the specific heat and λ is the heat conductivity coefficient. The thermal properties of water were assumed for the thermal properties of tissue.

A heat conductivity equation is calculated in cylindrical geometry for near vessel area, where the center of the cylinder was chosen as point with maximal temperature.

$$\rho c \partial T / \partial t = \lambda \partial^2 T / \partial x^2 + 1/r \cdot \partial T / \partial r + \gamma_s \psi_s$$

As one skilled in the art should recognize other models may be used as well.

The microprocessor or personal computer can also be used to create and store patient information in a database. Thus, past treatment information such as condition being treated, treatment parameters, number of treatments, etc. is stored and may be recalled when the patient is again treated. This aids in providing the proper treatment to the patient.

Additionally, the database may include photographs of the patient's condition before and after each treatment. Again, this aids in record keeping and determining what treatments are most successful for given conditions.

In addition to the treatments described above the devices and methods described herein may be used to treat other conditions. For example, psoriasis and warts have been successfully treated. Similarly, skin rejuvenation (treating wrinkles) should be effective. The inventor further contemplates using this invention to treat hemorrhoids, throat lesions, and gynecological problems associated with vascular malformations. In addition, hair depilation can also be effected.

In the use of hair depilation in accordance with the present invention, hair is removed by exposing the "hairy" area to intense, wide area, pulsed electromagnetic (light) energy. The energy heats the hair and coagulates the tissue around the hair and follicle without damaging the healthy skin.

An optically transparent water based gel may be applied to the skin prior to treatment. As used herein gel means a viscous fluid that is preferably, but not necessarily water based. The gel is used to cool the epidermis which is the primary location of light absorption by tissue, due to the melanin content of the epidermis. The gel is applied so as not to penetrate into the cavity generated by the hair follicle, and thus does not cool the hair and the hair follicle. As a result the energy is selectively applied to coagulate the hair without damaging the skin.

It is desirable that a spatially dispersed field of light be used for treatment of the skin, in accordance with the invention. By spatially dispersed, it is intended that the field of light

be spread over an extended area, as would be apparent from the term to one of ordinary skill in the art. Accordingly, any apparatus or combination of elements suitable for producing a dispersed field of light on the skin, as opposed to a narrow beam of light on the skin, can be used.

A polychromatic light source, such as a high intensity pulsed flashlamp, is an example of a source suitable for the purposes described herein. One advantage of a polychromatic source such as a flashlamp is that energy having a wavelength in the range of 550 to 630nm is heavily absorbed in blood and can be used to coagulate the vessel that feeds the hair. Additionally, longer wavelengths, in the range of 600 to 1100nm have a very good penetration into non-pigmented skin. This wavelength range can be used to couple to the melanin of the hair. The higher pigmentation of the hair and the hair follicle can enhance the absorption of energy by the hair.

Flashlamps also have the advantage of being able to illuminate a large area, thus minimizing the treatment time. The flashlamp combined with a proper reflector can deliver the required fluences to areas on the order of a few square centimeters in a single application. However, other light sources, such as pulsed lasers can be used as well.

Referring now to Figure 20, a schematic drawing of a cross section of a hair follicle 200 in a dermis 202 is shown. As may be seen in Figure 20, a gel 203 applied to an epidermis 204. In the present invention, water based transparent gel 203 is applied to a large section of the skin that is covered by hair, such as hair 205. Gel 203 is applied to epidermis 204 and creates a thin layer on top of epidermis 204. This layer is closely coupled to epidermis 204 and acts as a heat sink that cools epidermis 204 when light (electromagnetic

energy) is applied to the area. As may also be seen in Figure 20, gel 203 does not penetrate into a cavity 206 formed by hair follicle 200 due to its surface tension properties and the fact that the hair is naturally covered by a thin layer of fatty material which makes it hydrophobic. The much higher heat diffusivity of gel 203 compared to that of air which fills cavity 206 enables fast cooling of epidermis 204, represented by arrows 207, while hair 205 is cooled at a much slower rate.

The cooling time - δt of an object that has typical dimensions d and diffusivity - α can be written as:

$$\delta t = d^2 / 16\alpha$$

The epidermis has typical cross dimensions of less than 0.1 mm, which is also the typical diameter of hair. The diffusivity of water is approximately $\alpha = 3 \times 10^{-9} \text{ m}^2 \text{ sec}^{-1}$.

The gel is applied, in the manner shown in Figure 20, over a wide area. When the gel is so applied the typical cooling time of the hair will be on the order of 200 msec and that of the epidermis will be on the order of 5 msec. This difference in cooling times is due to the fact that the gel does not penetrate into the hair follicles. It is preferable to use a transparent gel since the gel acts only as a cooling agent and should not be heated by the external illumination.

In accordance with the invention, light is applied to the treated area in either a long pulse or in a sequence of pulses separated by a delay. The delay and/or pulse length is preferably controlled by the operator to provide enough heat to remove the hair but not enough heat to damage the skin. For example, the pulse length or delay between the pulses

should be more than the cooling time of the gel covered epidermis and less than the cooling time of the hair and follicle. Thus, referring to the above discussion on cooling times, a pulse length of 50msec if a single pulse is used or a delay of 50msec between the pulses if a pulse sequence is used are appropriate values. The spectrum of the light source may be selected with reference to the absorption by the skin, by the hair and by the blood vessels feeding the hair. For example, the hair follicle has typical a depth of 1 to 2 mm. It is preferable, therefore, to use a light wavelength range that can penetrate into this depth without very high attenuation.

Figure 21 is a graph showing the scattering, absorption and effective attenuation coefficients in fair skin dermis and the absorption coefficient of blood in the 400 to 1000nm range. Because a wide area is illuminated, rather than a single hair, it is preferable to use a wavelength range that penetrates into the skin without being highly attenuated. The skin attenuation coefficient controls the depth of penetration of light into the skin. As may be seen in Figure 21 wavelengths that are longer than 550nm will be more effective to penetrate deep enough into the skin. Shorter wavelengths are less desirable because they will be highly attenuated before reaching the lower parts of the hair follicles.

Wavelengths significantly longer than 1,000nm are also less effective due to high absorption of infrared in water which constitutes more than 70% of skin. Wide area photo thermal hair removal of the present invention preferably uses light that can penetrate deep into the skin, since light is coupled to the hair and the hair follicles only after it penetrates through the skin. Most of the spectrum of light at wavelengths longer than 1,300nm is heavily absorbed in water and will be less useful because it does not penetrate very deep into the

skin. For example, CO₂ laser radiation in the 10,000nm range penetrates only a few tens of microns into the skin.

Referring now to Figures 22 and 23, one preferred embodiment of hair remover 300 includes a flashlamp 301 located in a housing 302 having a handle. The flashlamp is shown adjacent gel 203 and hairy skin 202/204/205. One flashlamp that the inventors have found effective for hair removal is described in detail in co-pending United States Patent Application For Method and Apparatus For Therapeutic Electromagnetic Treatment, Serial No. 07/964,210, filed October 20, 1992 and issued as U.S. Patent No. 5,405,368, and incorporated herein by reference. The flashlamp described therein provides a suitable fluence and it illuminates a large area in a single pulse (on the order of 10X50 mm).

Such a flashlamp is driven by a variable pulse width power source. The flashlamp is contained in housing 302 and the light from the flashlamp is directed towards the skin by a reflector 305 that has a high reflectivity.

Also shown in Figures 22 and 23 is a filter 307, that is disposed between flashlamp 301 and gel 203. The filter, or in an alternative embodiment, multiple filters, are used to control the spectrum generated by the light source. As used herein filter, or band-pass filter, describes a device that allows electromagnetic energy (light) of certain wavelengths or frequencies to pass. The other wavelengths or frequencies are either partially or wholly removed.

The operator can select the filter according to the skin pigmentation of the person being treated. For the embodiment using a flashlamp, one can take advantage of the spectral range typically generated by such a lamp, which is in the range of 200 to 1300 nm for high

pressure xenon flashlamps operated at high current densities (on the order of 1,000 to 5,000 A/cm²). Since hair removal is mainly done for cosmetic reasons and is mostly important for cases of darker hair, the hair itself will absorb light in a wide spectral range in the visible and the near infrared. The shorter wavelengths generated by the flashlamp may be removed since they do not penetrate as deeply into the skin (as can be seen from Figure 21).

In one embodiment a long pass filter that transmits only wavelengths longer than the cut off wavelength of the filter is used. A cut off wavelength of 600nm is used in a preferred embodiment when the person being treated has fair skin. A cut off wavelength in the range of 700 to 800nm is used in the preferred embodiment to treat people with dark skin. According to the invention, the filters may be, for example, dichroic filters or absorbing filters. The desired spectrum can also be achieved by more than one filter or by band-pass filters.

Light from flashlamp 301 is coupled to the skin through a transparent window 308 and a coupler 310 (described below). As shown in Figures 22 and 23, window 308 is placed on transparent water based gel 203. In use, the operator holds hair remover 300 by handle 304, and places it on the area of skin where treatment is desired (and gel 203 has been applied). Transparent window 308 creates a well defined flat surface on gel 203, through which light enters into gel 203 and into the skin.

The operator selects the pulse and energy fluence parameters on a control unit (not shown). The power and control unit are preferably housed in a separate box and will include power from a capacitor charged to a high voltage by a DC power supply, wherein the capacitor is discharged through the flashlamp. Hair remover 300 can be connected to the power and control unit via a flexible cable that allows easy aiming of the device when aiming

it to the treatment area on the patient's skin. Pulse length control can be achieved by using a few pulse forming networks that can generate different pulse widths. Alternatively, an opening 309 may include a solid state opening switch that can stop the discharge at a time preset by the operator, thus controlling the pulse width. These elements of the device are well known and can be easily constructed, or replaced by similar elements, as one skilled in the art will know.

After the parameters have been selected, the operator fires the unit by pressing a switch that can be located in a variety of locations. A total fluence on the order of 10 to 100 J/cm² will successfully remove the hair. This fluence can be determined from the requirement of reaching a high enough temperature of the hair and hair follicle, and considering the penetration of light, through the skin and into the hair and hair follicle, absorption of light in the hair and hair follicle, specific heat capacity of the hair and the hair follicle, and the cooling of the hair during the pulse by heat conductivity to the surrounding skin.

Coupler 310 transmits light from flashlamp 301 to gel 203 and to the skin. The coupler can be comprised of a hollow box with internally reflecting walls that act as a light guide for the light generated by flashlamp 301, to transmit the light (electromagnetic energy) to the skin. Coupler 310 may alternatively be made from other material, for example, a solid transparent material such as glass or acrylic in which light reflection from the walls is achieved by using total internal reflection on the side walls.

Coupler 310 is used, in one alternative embodiment, to control the angular distribution of the light rays impinging on the skin. Light rays will hit the hair or the hair follicle predominantly when they are travelling in a direction perpendicular to the plane of the skin.

A distribution of light rays that has a relatively wide angular divergence when treating shallow hair is desirable to direct a large portion of the energy to the hairs and follicles. Conversely, a narrow divergence is preferable when deep penetration is desired.

In one embodiment both shallow and deep penetration is obtained by using a two stage treatment process. A narrow divergence beam is used first to treat the deeper hair follicles, while a high divergence beam is used to treat the top of the hair follicles.

Figure 24 shows a coupler 501 having an exit beam with a greater angular divergence than that of the entrance beam. As shown in Figure 24, a beam 502 enters coupler 501 at a small angle, relative to the axis of coupler 501. When beam 502 exits coupler 501 the angle, relative to the axis, is much greater. The tapered shape of coupler 501 enhances this divergence.

Figure 25 shows a straight coupler 601, that maintains the angular distribution of the rays of light that enter into it. A beam 602 is shown entering and exiting coupler 601 with the same angle, relative to the axis of coupler 601. Alternate use of both couplers 501 and 601 can achieve the narrow and deep penetration discussed above. Alternatively, the user can select the type of coupler according to the depth of hair being treated.

Clinical tests have been performed on hair on the legs of a few patients. Hair was removed for at least two months without observing any hair growing back on the exposed areas during this period. The experiments were performed with high fluences, i.e., up to 45 J/cm² in each exposure. The spectrum used covered the range of 570 to 1100 nm and the fluence was supplied in a triple pulse with delays of 50 to 100 msec between pulses. The pulse sequence enabled hair removal with minimum pain and no damage to the skin. The

transparent gel that was used in these experiments was a water based ultrasound gel, such as that commonly available.

Thus, it should be apparent that there has been provided in accordance with the present invention various inventions that fully satisfy the objectives and advantages set forth above. Although the inventions have been described in conjunction with specific embodiments thereof, it is evident that many alternatives, modifications and variations will be apparent to those skilled in the art. Accordingly, it is intended to embrace all such alternatives, modifications and variations that fall within the spirit and broad scope of the appended claims.

Claims

1. A medical treatment device for application of light to the skin, comprising:
 - a light source for creating a spatially dispersed field of light;
 - a power source for providing power to said light source; and
 - an optically transparent medium for contact with the skin to transmit said light to said skin.
2. A device as claimed in Claim 1, wherein said medium comprises a transparent plate.
3. A device as claimed in Claim 1, wherein said medium comprises a gel.
4. A device as claimed in Claim 1, wherein said medium comprises a transparent plate, and further comprises a gel beneath said transparent plate.
5. A device as claimed in Claim 1, further comprising at least one element for directing light from said spatially dispersed field of light.
6. A device as claimed in Claim 5, wherein said element is a reflector.
7. A medical system for improving the appearance of the skin, comprising:
 - a light source for generating optical radiation;
 - a contact device, said contact device comprising a first transparent medium for placement in contact with the skin for transmission of said optical radiation; and,
 - a second optically transparent medium for placement between said contact device and the skin, to transmit optical radiation from said contact device to the skin.
8. A medical system as claimed in Claim 7, wherein said light source generates a spatially dispersed field of light.
9. A medical system as claimed in Claim 7, wherein said light source comprises a flashlamp.

10. A medical system as claimed in Claim 7, wherein said light source produces incoherent light.
11. A medical system as claimed in Claim 7, wherein said light source produces pulses of light.
12. A medical system as claimed in Claim 7, wherein said light source produces pulses of incoherent light.
13. A medical system as claimed in Claim 7, wherein said first transparent medium comprises glass.
14. A medical system as claimed in Claim 7, wherein said second optically transparent medium comprises a gel.
15. A medical system as claimed in Claim 13, wherein said second optically transparent medium comprises a gel.
16. A medical system for application of light to the skin, comprising:
- an apparatus for producing a spatially dispersed field of light;
 - at least one element for directing said spatially dispersed field of light; and,
 - a transparent contact device in contact with the skin, for transmission of said light to the skin.
17. A medical systems as claimed in Claim 16, further comprising an optically transparent material for placement between said transparent contact device and the skin to transmit said light from said transparent contact device to the skin.
18. A medical system as claimed in Claim 17, further comprising a power source for providing power to said apparatus.
19. A medical system for application of light to the skin, comprising:
- an apparatus for producing a spatially dispersed field of light;

at least one element for directing said light;

a transparent contact device comprising an optically transparent material for placement in

contact with the skin for transmission of said light to the skin; and,

a transparent medium for placement between said contact device and the skin.

20. A medical system as claimed in Claim 19, wherein said transparent medium comprises a gel.

21. A medical system as claimed in Claim 19, wherein said apparatus can produce an energy density of 30-100 J/cm².

22. A medical system as claimed in Claim 19, wherein said apparatus can produce pulsed light.

23. A method for medical application of light to the skin, comprising:

providing a light source for generating optical radiation;

providing a contact device, said contact device comprising a first optically transparent medium;

placing said contact device on the skin; and,

transmitting optical radiation from said light source to said contact device to the skin.

24. A method as claimed in Claim 23, further comprising the steps of:

providing a second optically transparent medium; and,

placing said second optically transparent medium between said contact device and the skin;

wherein said step of transmitting optical radiation from said contact device to the skin

comprises transmission of optical radiation from said contact device to second optically

transparent medium and transmission of optical radiation from said second optically

transparent medium to the skin.

25. A method as claimed in Claim 23, wherein said light is applied for hair depilation.
26. A method as claimed in Claim 24, wherein said light is applied for hair depilation.
27. A method as claimed in Claim 23, wherein said light is applied to improve the appearance of the appearance of the skin.
28. A method as claimed in Claim 24, wherein said light is applied to improve the appearance of the skin.

Abstract

Apparatus and methods for electromagnetic skin treatment, including the removal of hair. Devices include pulsed light sources such as flashlamps for providing electromagnetic treatment of the skin, including hair removal. The devices and methods provide for the removal of large numbers of hairs at the same time, rather than on a hair by hair basis.

607
054

330
1-13






FIG. 3




FIG. 4




FIG. 5




FIG. 6




FIG. 7




FIG. 8

004720-8650560




FIG. 9




FIG. 10




FIG. 11




FIG. 12




FIG. 13




FIG. 14




FIG. 15




FIG. 15




FIG. 17




FIG. 18




FIG. 19




FIGURE 20

Skin Optical Properties




FIGURE 21




FIGURE 22




FIGURE 1 23




FIGURE 24




FIGURE 25

Declaration and Power of Attorney For Patent Application

English Language Declaration

As a below named inventor, I hereby declare that:

My residence, post office address and citizenship are as stated below next to my name,

I believe I am the original, first and sole inventor (if only one name is listed below) or an original, first and joint inventor (if plural names are listed below) of the subject matter which is claimed and for which a patent is sought on the invention entitled

METHOD AND APPARATUS FOR ELECTROMAGNETIC TREATMENT OF THE SKIN, INCLUDING HAIR DEPILATION

the specification of which

(check one)

☒ is attached hereto.

☐ was filed on _____ as United States Application No. or PCT International Application Number _____ and was amended on _____ (if applicable)

I hereby state that I have reviewed and understand the contents of the above identified specification, including the claims, as amended by any amendment referred to above.

I acknowledge the duty to disclose to the United States Patent and Trademark Office all information known to me to be material to patentability as defined in Title 37, Code of Federal Regulations, Section 1.56.

I hereby claim foreign priority benefits under Title 35, United States Code, Section 119(a)-(d) or Section 365(b) of any foreign application(s) for patent or inventor's certificate, or Section 365(a) of any PCT International application which designated at least one country other than the United States, listed below and have also identified below, by checking the box, any foreign application for patent or inventor's certificate or PCT International application having a filing date before that of the application on which priority is claimed.

Prior Foreign Application(s)

Priority Not Claimed

_____ (Number)	_____ (Country)	_____ (Day/Month/Year Filed)	<input type="checkbox"/>
_____ (Number)	_____ (Country)	_____ (Day/Month/Year Filed)	<input type="checkbox"/>
_____ (Number)	_____ (Country)	_____ (Day/Month/Year Filed)	<input type="checkbox"/>

I hereby claim the benefit under 35 U.S.C. Section 119(e) of any United States provisional application(s) listed below:

_____ (Application Serial No.)	_____ (Filing Date)
_____ (Application Serial No.)	_____ (Filing Date)
_____ (Application Serial No.)	_____ (Filing Date)

I hereby claim the benefit under 35 U. S. C. Section 120 of any United States application(s), or Section 365(c) of any PCT International application designating the United States, listed below and, insofar as the subject matter of each of the claims of this application is not disclosed in the prior United States or PCT International application in the manner provided by the first paragraph of 35 U.S.C. Section 112. I acknowledge the duty to disclose to the United States Patent and Trademark Office all information known to me to be material to patentability as defined in Title 37, C. F. R., Section 1.56 which became available between the filing date of the prior application and the national or PCT International filing date of this application:

_____ 08/508,129 (Application Serial No.)	_____ 7/27/95 (Filing Date)	_____ Pending (Status) (patented, pending, abandoned)
_____ 08/412,519 (Application Serial No.)	_____ 3/29/95 (Filing Date)	_____ Pending (Status) (patented, pending, abandoned)
_____ (Application Serial No.)	_____ (Filing Date)	_____ (Status) (patented, pending, abandoned)

I hereby declare that all statements made herein of my own knowledge are true and that all statements made on information and belief are believed to be true; and further that these statements were made with the knowledge that willful false statements and the like so made are punishable by fine or imprisonment, or both, under Section 1001 of Title 18 of the United States Code and that such willful false statements may jeopardize the validity of the application or any patent issued thereon.

POWER OF ATTORNEY: As a named inventor, I hereby appoint the following attorney(s) and/or agent(s) to prosecute this application and transact all business in the Patent and Trademark Office connected therewith. (list name and registration number)

Andrew S. Langsam (Reg. No. 28,556)

Peter L. Berger (Reg. No. 24,570)

Morris E. Cohen (Reg. No. 39,947)

Barry E. Negrin (Reg. No. 37,407)

Send Correspondence to: Andrew S. Langsam, Esq.
Levisohn, Lerner, Berger and Langsam
75 Third Avenue, Suite 2400
New York, New York 10017

Direct Telephone Calls to: (name and telephone number)
Andrew S. Langsam - (212) 486-7272

Full name of sole or first inventor Shimon Eckhouse	
Sole or first inventor's S. L.	Date August 13, 1997
Residence Israel	
Citizenship Israel	
Post Office Address 27 Ester-Rabin Street	
Haifa, Israel 34987	

Full name of second inventor, if any Hillel Bachrach	
Second inventor's signature [Signature]	Date August 13, 1997
Residence USA	
Citizenship ISRAEL	
Post Office Address c/o ESC, Inc.	
100 Crescent Road, Needham, MA 02194	